

TR 459 - Especificações técnicas



Description

TR 459 foi projetado especificadamente para operações de escavação e carga, bem como para aplicações no setor da municipalidade e na manutenção com tratores e retroscavadoras. O pneu proporciona uma estabilidade elevada e está disponível em duas versões. A versão "special" garante um ciclo de vida prolongado do pneu.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Retroscavadora • Trator
Industrial: Retroscavadora

Version	INDUSTRIAL
Type	TL
Tyre Size	16.9 - 24
LI/SS	145 A8

Dimensions International Standard

Ply Rating	10
Section Width (mm)	450
Overall Diameter (mm)	1310
Static Loaded Radius (mm)	590
Rolling Circumference (mm)	3850
Rim Rec	DW 15 L
Rim Alt	DW 14 L
ECE	E11-106R-005211
TRA Code	R4

Load capacity (Kg)

km/h / bar	2.20
40	2900

Printed on 26/04/2024 10:34

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..