

TR 459 - Especificações técnicas



Description

TR 459 foi projetado especificadamente para operações de escavação e carga, bem como para aplicações no setor da municipalidade e na manutenção com tratores e retroscavadoras. O pneu proporciona uma estabilidade elevada e está disponível em duas versões. A versão "special" garante um ciclo de vida prolongado do pneu.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Retroscavadora • Trator
Industrial: Retroscavadora

Version	INDUSTRIAL
Type	TL
Tyre Size	18.4 - 26
LI/SS	159 A8

Dimensions US Standard

Usa code	94016631
Ply Rating	14
Section Width (inch)	18.6
Overall Diameter (inch)	56.1
Static Loaded Radius (inch)	24.7
Rolling Circumference (inch)	171.1
Rim Rec	DW 16 L
Rim Alt	DW 15 L
ECE	E11-106R-003396
TRA Code	R4

Load capacity (lbs)

mph / psi	42
25	9650

Printed on 26/04/2024 12:05

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..