

## TR 459 - Especificações técnicas



### Description

TR 459 foi projetado especificadamente para operações de escavação e carga, bem como para aplicações no setor da municipalidade e na manutenção com tratores e retroescavadoras. O pneu proporciona uma estabilidade elevada e está disponível em duas versões. A versão "special" garante um ciclo de vida prolongado do pneu.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricultura: Retroescavadora • Trator  
Industrial: Retroescavadora

Version	INDUSTRIAL
Type	TL
Tyre Size	19.5L - 24
LI/SS	147 A8

## Dimensions International Standard

Ply Rating	10
Section Width (mm)	490
Overall Diameter (mm)	1333
Static Loaded Radius (mm)	585
Rolling Circumference (mm)	4031
Rim Rec	DW 16 L
ECE	E11-106R-005334
TRA Code	R4

## Load capacity (Kg)

km/h / bar	1.90
40	3075

Printed on 26/04/2024 04:45

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..