

TR 461 - Especificações técnicas



Description

TR 461 é um pneu BKT desenvolvido para as aplicações em obras municipais e na manutenção com tratores, bem como para as operações de carga com levantadores telescópicos. A proteção do flanco é caracterizada pela resistência especial a cortes e lacerações, que garante uma vida mais longa do pneu, mesmo em superfícies duras junto com uma estabilidade excelente.

UM

International Standard

Construction

 BIAS

Machinery

Industrial: Retroescavadora • Levantador telescópico • Trator

Version	STANDARD
Type	TL
Tyre Size	16.9 - 24
LI/SS	151 A8

Dimensions International Standard

Ply Rating	14
Section Width (mm)	440
Overall Diameter (mm)	1280
Static Loaded Radius (mm)	566
Rolling Circumference (mm)	3763
Rim Rec	DW 15 L
Rim Alt	DW 14 L
TRA Code	R4

Load capacity (Kg)

km/h / bar	2.90
40	3450

Printed on 20/04/2024 00:41

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..