

## TR 675 - Dados técnicos



### Description

O TR 675 é um pneu diagonal desenhado especificamente para utilização na exploração florestal. O design de porca robusto proporciona excelente tração e autolimpeza. A forte estrutura da lona de carcaça permite o transporte de cargas pesadas, e as lonas de cima de aço protegem o pneu de furos e danos.

O TR 675 está dotado de um composto de piso resistente a cortes, para excelente resistência a cortes e aparas em terrenos difíceis, sob condições extremas.

### UM

International Standard

### Construction

✦ BIAS

### Machinery

Agricultura: Autocarregadora

SIZE	Version	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
540/65 - 28	STEEL BELTED	LS2	155 A8/161 A2	16	W 16 L	W 18 L	530	1425	663	4440	TL	E11-106R-005271

Printed on 25/04/2024 17:42

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..