

TRAC FARM PLUS - Especificações técnicas



Description

TRAC FARM PLUS é um pneu traseiro para tratores, especialmente projetado para trabalhar o terreno e para as operações de transporte. O pneu destaca-se pelo piso do pneu mais profundo, com barras de ângulo duplo, de modo a assegurar tanto uma tração excelente como uma condução confortável na estrada. O desenho especial do pneu proporciona um maior contacto para uma melhor estabilidade e ótimas propriedades de autolimpagem. TRAC FARM PLUS assegura um ciclo prolongado de vida do pneu.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Trator

Version	STANDARD
Type	TT
Tyre Size	13.6 - 28
LI/SS	128 A6

Dimensions International Standard

Ply Rating	12
Section Width (mm)	365
Overall Diameter (mm)	1345
Static Loaded Radius (mm)	621
Rolling Circumference (mm)	4088
Rim Rec	W 12
Rim Alt	W 11
ECE	E11-106R-004527
TRA Code	R1

Load capacity (Kg)

km/h / bar	2.30
30	1800

Printed on 03/12/2023 14:37

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..