

TRAC FARM - Especificações técnicas



Description

TRAC FARM é um pneu para operações de serviço pesado, especificadamente projetado para tratores e aplicações para trabalhar o terreno e de transporte. O piso profundo e o composto de borracha resistente a todos os tipos de cortes tornam este pneu apropriado para as condições operacionais mais difíceis, garantindo o melhor rendimento sobre o investimento durante todo o ciclo de vida do produto. TRAC FARM foi projetado com um maior número de barras que fornecem uma tração excelente e ótimas propriedades de autolimpagem.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Trator

Version	STANDARD
Type	TT
Tyre Size	12.4 - 28
LI/SS	122 A8

Dimensions US Standard

Usa code	94040322
Ply Rating	12
Section Width (inch)	12.6
Overall Diameter (inch)	51
Static Loaded Radius (inch)	23.7
Rolling Circumference (inch)	153.1
Rim Rec	W 11
Rim Alt	W 9 ; W 10
ECE	E11-106R-003562
TRA Code	R1

Load capacity (lbs)

mph / psi	36
25	3300

Printed on 19/04/2024 16:50

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..