

TRAC GRADER + - Especificações técnicas



Description

TRAC GRADER + (G-2) é um pneu de lonas cruzadas para motoniveladoras, que representa uma escolha excelente para os clientes orientados par ao orçamento. A carcaça durável foi projetada para resistir no tempo. O desenho de autolimpeza do piso revela uma proporção barras-espaço que fornece uma melhor tração em todas as condições. A versão "special" é realizada com um composto de borracha especial, resistente a cortes e rasgões.

UM

US Standard

Construction

 BIAS

Machinery

OTR: Motoniveladora

Version	SPECIAL
Type	TL
Tyre Size	14.00 - 24

Dimensions US Standard

Usa code	94014699
Ply Rating	12
Overall Width (inch)	14.3
Overall Diameter (inch)	53.1
Static Loaded Radius (inch)	23.5
Rolling Circumference (inch)	157.1
Rim Rec	8.00 TG SDC
Rim Alt	9.00/1.5 (DC) ; 10.00/VA SDC; 10.00 WA SDC
TRA Code	G2

Load capacity (lbs)

mph / psi	36
25	6800

Printed on 25/04/2024 11:26

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..