

## TRAC MASTER - Especificações técnicas



### Description

TRAC MASTER é um pneu para trabalhar a terra e para as aplicações em prados e jardinagem, apropriados para tratores pequenos e implementos agrícolas. O desenho do piso do pneu assegura uma excelente proteção de campo, a melhor tração no campo e propriedades de autolimpagem.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricultura: Implementos agrícolas • Trator pequeno

Version	STANDARD
Type	TL
Tyre Size	300/60 - 12

## Dimensions International Standard

Ply Rating	8
Section Width (mm)	306
Overall Diameter (mm)	645
Static Loaded Radius (mm)	285
Rolling Circumference (mm)	1885
Rim Rec	10.5
Rim Alt	9.5
ECE	E11-106R-003597

## Load capacity (Kg)

km/h / bar	3.20
50	1030

Printed on 26/04/2024 05:33

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..