

TRAC SUPER - Especificações técnicas



Description

TRAC SUPER é o primeiro pneu radial introduzido pela BKT no segmento da municipalidade. A estrutura do pneu com cintos de aço assegura uma ótima condução plana associada a melhores prestações de tração. Portanto, o pneu é apropriado particularmente para aplicações em superfícies de vastos prados, como nos parques e ao longo da estrada.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Trator pequeno

Version	STANDARD
Type	TL
Tyre Size	500/50 R 17
LI/SS	147 D

Dimensions US Standard

Usa code	94073337
Section Width (inch)	19.3
Overall Diameter (inch)	37
Static Loaded Radius (inch)	16.7
Rolling Circumference (inch)	112.2
Rim Rec	16.00
ECE	E11-106R-007767

Load capacity (lbs)

mph / psi	12	15	17	23	29	35	41	46	52
40	2650	3200	3680	4280	4820	5300	5840	6390	6780
25	3610	4350	4990	5820	6560	7200	7940	8680	9230
20	4010	4820	5540	6460	7280	8000	8810	9640	10240
5	4770	5750	6600	7700	8670	9530	10510	11480	12210

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 07/12/2024 22:01

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..