


TUF LUG - Especificações técnicas



Description

TUF LUG é apropriado para reboques e caminhões ligeiros nas aplicações de transporte. O pneu proporciona uma ótima tração e uma extraordinária duração, assegurando um longo ciclo de vida do produto.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Camião ligeiro • Reboque
Industrial: Camião ligeiro • Reboque

Version	STANDARD
Type	TT
Tyre Size	7.50 - 16

Dimensions US Standard

Usa code	94014316
Ply Rating	14
Section Width (inch)	8.5
Overall Diameter (inch)	32.7
Rim Rec	6.00 G
Rim Alt	5.50 F

Load capacity (lbs)

mph / psi	100
62 LS	3305
62 LD	2910

Printed on 26/04/2024 08:33

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..