

## VIJETA - Especificações técnicas



### Description

VIJETA é um pneu agrícola apropriado para aplicações na estrada e fora da estrada. O desenho do piso com nervura de 5 costelas otimiza a distribuição da carga. Além disso, o composto de borracha, resistente ao desgaste e a carcaça robusta garantem um longo ciclo de vida do pneu.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agricultura: Reboque

|           |           |
|-----------|-----------|
| Version   | STANDARD  |
| Type      | TT        |
| Tyre Size | 6.00 - 19 |
| LI/SS     | 105 A3    |

## Dimensions US Standard

|                         |          |
|-------------------------|----------|
| Usa code                | 94052356 |
| Ply Rating              | 8        |
| Section Width (inch)    | 6.9      |
| Overall Diameter (inch) | 31.9     |
| Rim Rec                 | 4.00     |

## Load capacity (lbs)

|  |           |      |
|--|-----------|------|
|  | mph / psi | 60   |
|  | 10        | 2040 |

Printed on 20/04/2024 11:03

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..