

W 207 - Dados técnicos



Description

W 207 é o pneu BKT para aplicações desportivas todo-o-terreno. Graças à tecnologia M+S e o desenho especial, assegura uma tração excelente em todas as condições. O pneu destaca-se pela resistência excelente à perfuração em terrenos mais insidiosos.

UM

International Standard

Construction

✚ BIAS

Machinery

Agricultura: Veículo ATV

SIZE	Version	PR	RIM REC	RIM ALT	SW	OD	Type	ECE
AT 22 X 11 - 8	STANDARD	6	9.0 AT	8.5 AT	272	561	TL	E4-75R-0004984-01
AT 22 X 11 - 9	STANDARD	6	9.0 AT	8.5 AT	272	561	TL	E4-75R-0004985-01
AT 25 X 12 - 9	STANDARD	6	9.5 AT	9.0 AT ; 10.0 AT	300	632	TL	E11-75R-004629
AT 25 X 13 - 9	STANDARD	6	10.5 AT	10.0 AT	330	635	TL	
AT 22 X 11 - 10	STANDARD	6	9.0 AT	8.5 AT	272	561	TL	E4-75R-0006333
AT 22 X 7 - 10	STANDARD	6	5.5 AT	6.0 AT	178	559	TL	E4-75R-0006331
AT 22 X 8 - 10	STANDARD	6	6.5 AT	6.0 AT	203	559	TL	E4-75R-0004981-01
AT 23 X 10 - 10	STANDARD	6	8.0 AT	7.5 AT ; 8.5 AT	249	587	TL	
AT 23 X 7 - 10	STANDARD	6	5.5 AT	6.0 AT	177	584	TL	E4-75R-0006335
AT 23 X 8 - 10	STANDARD	6	6.5 AT	6.0 AT	203	589	TL	
AT 24 X 11 - 10	STANDARD	6	9.0 AT	8.5 AT	279	610	TL	E4-75R-0004987-01
AT 25 X 11 - 10	STANDARD	6	9.0 AT	8.5 AT	285	640	TL	E11-75R-004673
AT 25 X 12 - 10	STANDARD	6	9.5 AT	9.0 AT ; 10.0 AT	297	640	TL	
AT 23 X 8 - 11	STANDARD	6	6.5 AT	6.0 AT	203	584	TL	
AT 24 X 10 - 11	STANDARD	6	8.0 AT	7.5 AT ; 8.5 AT	249	612	TL	
AT 24 X 8 - 11	STANDARD	6	6.5 AT	6.0 AT	203	612	TL	
AT 24 X 9 - 11	STANDARD	6	7.0 AT	7.5 AT	226	610	TL	
AT 25 X 10 - 11	STANDARD	6	8.0 AT	7.5 AT ; 8.5 AT	249	638	TL	
AT 25 X 8 - 11	STANDARD	6	6.5 AT	6.0 AT	203	638	TL	
AT 24 X 8 - 12	STANDARD	6	6.5 AT	6.0 AT	198	615	TL	E11-75R-005007
AT 25 X 10 - 12	STANDARD	6	8.0 AT	6.5 AT ; 7.5 AT ; 8.5 AT	249	638	TL	E4-75R-0004991
AT 25 X 11 - 12	STANDARD	6	9.0 AT	8.5 AT	284	638	TL	E11-75R-004674
AT 25 X 8 - 12	STANDARD	6	6.5 AT	6.0 AT	198	638	TL	E4-75R-0004981-01
AT 26 X 10 - 12	STANDARD	6	8.0 AT	7.5 AT ; 8.5 AT	241	658	TL	E4-75R-0006336
AT 26 X 12 - 12	STANDARD	6	9.5 AT	8.0 AT ; 8.5 AT ; 9.0 AT	299	658	TL	E4-75R-0006337
AT 26 X 8 - 12	STANDARD	6	6.50 AT	6.00 AT	204	660	TL	E11-75R-005008
AT 27 X 10 - 12	STANDARD	6	8.0 AT	7.5 AT ; 8.5 AT	241	683	TL	E4-75R-0006338
AT 27 X 12 - 12	STANDARD	6	9.5 AT	8.5 AT ; 9.0 AT	299	683	TL	E4-75R-0006339
AT 28 X 10 - 12	STANDARD	6	8.0 AT	7.5 AT ; 8.5 AT	241	706	TL	E4-75R-0006340
AT 28 X 12 - 12	STANDARD	6	9.5 AT	8.5 AT ; 9.0 AT	299	706	TL	E4-75R-0006341

Printed on 03/05/2024 21:19

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..