

## XL GRIP (ADT) - Especificações técnicas



### Description

O XL GRIP (ADT) é um pneu diagonal para camiões basculantes articulados concebido para minimizar os custos e furos em condições difíceis onde se exige tração excecional. Estas características garantem a duração alargada do pneu.

### UM

International Standard

### Construction

 BIAS

### Machinery

OTR: Dumper Articulado

Version	STANDARD
Type	TL
Tyre Size	29.5 - 25

## Dimensions International Standard

<b>Ply Rating</b>	32
<b>Overall Width (mm)</b>	760
<b>Overall Diameter (mm)</b>	1860
<b>Static Loaded Radius (mm)</b>	849
<b>Rolling Circumference (mm)</b>	5544
<b>Rim Rec</b>	25.00/3.5
<b>TRA Code</b>	E3

## Load capacity (Kg)

<b>km/h / bar</b>	<b>3.75</b>
<b>50</b>	<b>12500</b>

Printed on 23/04/2024 14:30

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..