

## XL GRIP (BHL) - Especificações técnicas



### Description

XL GRIP (BHL) foi especialmente desenvolvido para retroscavadoras que são utilizadas em operações pesadas nas aplicações de escavação, terraplanagem e carregamento. O desenho não direcional do piso do pneu assegura uma ótima tração e estabilidade. O especial composto de borracha do piso traduz-se numa resistência excelente a cortes e lacerações e prolonga a vida do piso do pneu.

### UM

US Standard

### Construction

 BIAS

### Machinery

Industrial: Retroscavadora

Version	INDUSTRIAL
Type	TT
Tyre Size	14.9 - 24
LI/SS	145 A8

## Dimensions US Standard

Usa code	94045396
Ply Rating	12
Section Width (inch)	15
Overall Diameter (inch)	48.8
Static Loaded Radius (inch)	22.6
Rolling Circumference (inch)	143.5
Rim Rec	DW 13
Rim Alt	DW 11 ; DW 12 ; DW 13L

## Load capacity (lbs)

mph / psi	42
25	6400

Printed on 25/04/2024 05:51

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..