

XL GRIP (E3) - Especificações técnicas



Description

XL GRIP (E-3) é um pneu de lonas cruzadas para dumper rígidos, projetado devidamente para minimizar o risco de cortes e perfurações em condições que exigem uma tração excepcional. Estas características conferem ao pneu uma vida prolongada.

UM

US Standard

Construction

✚ BIAS

Machinery

OTR: Dumper Rígido

Version	STANDARD
Type	TL
Tyre Size	18.00 - 25

Dimensions US Standard

Usa code	94043347
Ply Rating	16
Overall Width (inch)	20.1
Overall Diameter (inch)	63.6
Static Loaded Radius (inch)	29.1
Rolling Circumference (inch)	188.2
Rim Rec	13.00/2.5
Rim Alt	15.00/2.5
TRA Code	E3/L3
Tread Depth	40

Load capacity (lbs)

mph / psi	40	54
30	12300	-
5	-	22000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 10/05/2025 03:27

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..