

XL GRIP IND3 (ECH) - Especificações técnicas



Description

XL GRIP (IND-3) é um pneu de lonas cruzadas para unidades de movimentação para contentores vazios nas aplicações de empilhamento e levantamento. O pneu é caracterizado por uma carcaça robusta que fornece uma durabilidade prolongada e uma estabilidade elevada em modalidade de elevação.

UM

International Standard

Construction

 BIAS

Machinery

Industrial: Movimentador para contentores vazios

Version	INDUSTRIAL
Type	TL
Tyre Size	16.00 - 25

Dimensions International Standard

Ply Rating	28
Overall Width (mm)	465
Overall Diameter (mm)	1485
Static Loaded Radius (mm)	682
Rolling Circumference (mm)	4395
Rim Rec	11.25/2.0
Rim Alt	13.00/2.0
TRA Code	IND3

Load capacity (Kg)

km/h / bar	9.00
10	15525

Printed on 19/04/2024 03:28

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..