

## XL GRIP IND3 (ECH) - Especificações técnicas



### Description

XL GRIP (IND-3) é um pneu de lonas cruzadas para unidades de movimentação para contentores vazios nas aplicações de empilhamento e levantamento. O pneu é caracterizado por uma carcaça robusta que fornece uma durabilidade prolongada e uma estabilidade elevada em modalidade de elevação.

### UM

US Standard

### Construction

 BIAS

### Machinery

Industrial: Movimentador para contentores vazios

Version	PORT INDUSTRIAL
Type	TL
Tyre Size	18.00 - 25

## Dimensions US Standard

Usa code	94049042
Ply Rating	40
Overall Width (inch)	20.1
Overall Diameter (inch)	63.6
Static Loaded Radius (inch)	29.1
Rolling Circumference (inch)	188.2
Rim Rec	13.00/2.5
Rim Alt	15.00/2.5
TRA Code	IND3

## Load capacity (lbs)

mph / psi	145
5	50600

Printed on 19/04/2024 03:42

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..