

XL GRIP IND3 (RTG) - Especificações técnicas



Description

XL GRIP (IND-3) é um pneu de lonas cruzadas para guindastes RTG nas aplicações de empilhamento e levantamento. O pneu é caracterizado por uma carcaça robusta realizada com um composto devidamente formulado que fornece um ciclo de vida prolongado do pneu.

UM

International Standard

Construction

 BIAS

Machinery

Industrial: Guindaste RTG

Version	INDUSTRIAL
Type	TL
Tyre Size	21.00 - 25

Dimensions International Standard

Ply Rating	32
Overall Width (mm)	576
Overall Diameter (mm)	1750
Static Loaded Radius (mm)	789
Rolling Circumference (mm)	5185
Rim Rec	15.00/3.0
Rim Alt	17.00/3.0
TRA Code	IND3

Load capacity (Kg)

km/h / bar	7.80
10	24000

Printed on 18/04/2024 05:25

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..