

XL GRIP IND3 (RTG) - Especificações técnicas



Description

XL GRIP (IND-3) é um pneu de lonas cruzadas para guindastes RTG nas aplicações de empilhamento e levantamento. O pneu é caracterizado por uma carcaça robusta realizada com um composto devidamente formulado que fornece um ciclo de vida prolongado do pneu.

UM

US Standard

Construction

 BIAS

Machinery

Industrial: Guindaste RTG

Version	INDUSTRIAL
Type	TL
Tyre Size	24.00 - 29

Dimensions US Standard

Usa code	94041343
Ply Rating	42
Overall Width (inch)	25.8
Overall Diameter (inch)	78.5
Static Loaded Radius (inch)	35.4
Rolling Circumference (inch)	230.7
Rim Rec	17.00/3.5
TRA Code	IND3

Load capacity (lbs)

mph / psi	130
5	79900
15	74000

Printed on 18/04/2024 09:22

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..