

XL GRIP (L3) - Especificações técnicas



Description

XL GRIP (E-3/L-3) é um pneu de lonas cruzadas de base larga (wide), concebido para carregadores, com vista a minimizar o risco de cortes e perfurações nas aplicações pesadas de carga. O pneu assegura uma tração excelente, bem como um ciclo de vida prolongado do produto.

UM

US Standard

Construction

❖ BIAS

Machinery

Industrial: Carregadora

OTR: Trator de esteira • Carregadora

Version	DUAL BEAD
Type	TL
Tyre Size	17.5 - 25

Dimensions US Standard

Usa code	94063406
Ply Rating	24
Overall Width (inch)	17.1
Overall Diameter (inch)	53
Static Loaded Radius (inch)	24.5
Rolling Circumference (inch)	156.7
Rim Rec	14.00/1.5
TRA Code	E3/L3

Load capacity (lbs)

mph / psi	84	102
30	13550	-
5	-	22000

Printed on 19/04/2024 21:21

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..