

XL GRIP (SCRAPER) - Especificações técnicas



Description

XL GRIP (SCRAPER) é o pneu de base larga não direcional para scraper em qualquer terreno. O pneu é caracterizado por uma carcaça robusta e um composto devidamente formulado que asseguram uma resistência excelente a cortes e lacerações também durante condições de serviço pesadas. Vantagens adicionais são ótimas qualidades de autolimpagem e uma estabilidade extraordinária.

UM

US Standard

Construction

 BIAS

Machinery

OTR: Raspador

Version	STANDARD
Type	TL
Tyre Size	29.5 - 29

Dimensions US Standard

Usa code	94063604
Ply Rating	28
Overall Width (inch)	29.9
Overall Diameter (inch)	77.4
Rim Rec	25.00/3.5
Rim Alt	26.00/3.5
TRA Code	E3

Load capacity (lbs)

mph / psi	47	62
30	26800	-
5	-	41900

Printed on 26/04/2024 10:47

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..