

XL GRIP (T) - Especificações técnicas



Description

XL GRIP (E-3) é muito apropriado para dumper com caixa basculante que transporta cargas pesadas nas aplicações nas minas. O composto de borracha do pneu é concebido para minimizar o risco de cortes e perfurações nos terrenos mais difíceis. XL GRIP (E-3) proporciona uma tração excelente, assegurando um ciclo de vida prolongado do pneu.

UM

US Standard

Construction

 BIAS

Machinery

OTR: Camião basculante

Version	STANDARD
Type	TT
Tyre Size	12.00 - 20

Dimensions US Standard

Usa code	94047840
Ply Rating	20
Overall Width (inch)	12.6
Overall Diameter (inch)	45.5
Static Loaded Radius (inch)	21.5
Rolling Circumference (inch)	136.4
Rim Rec	8.5
Rim Alt	8.0

Load capacity (lbs)

mph / psi	110
55 LS/LD	7610

Printed on 27/04/2024 11:38

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..