

XL GRIP (T) - Dados técnicos



Description

XL GRIP (E-3) é muito apropriado para dumper com caixa basculante que transporta cargas pesadas nas aplicações nas minas. O composto de borracha do pneu é concebido para minimizar o risco de cortes e perfurações nos terrenos mais difíceis. XL GRIP (E-3) proporciona uma tração excelente, assegurando um ciclo de vida prolongado do pneu.

UM

US Standard

Construction

 BIAS

Machinery

OTR: Camião basculante

SIZE	Version	USACode	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
8.25 - 16	STANDARD	94060832	16	6.50 H	6.00 G	9.4	34.3	0	0	TT
10.00 - 20	STANDARD	94015665	18	7.5	7.0	11.2	42.3	19.9	128.2	TT
11.00 - 20	STANDARD	94029358	18	8.0	7.5	11.7	43.9	20.8	132.6	TT
12.00 - 20	STANDARD	94047789	18	8.5	8.0	12.6	45.5	21.5	136.4	TT
12.00 - 20	STANDARD	94047840	20	8.5	8.0	12.6	45.5	21.5	136.4	TT
12.00 - 20	STANDARD	94061914	24	8.5	8.0	12.6	45.5	21.5	136.4	TT
12.00 - 24	STANDARD	94015672	20	8.5	8.0	12.6	49.2	23	146.1	TT
12.00 - 24	STANDARD	94027590	20	8.5	8.0	12.6	49.2	23	146.1	TL
12.00 - 24	STANDARD	94031122	24	8.5	8.0	12.6	49.2	23	146.1	TT

Printed on 27/04/2024 12:31

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..