XL GRIP ULTRA - Especificações técnicas

Description

XL GRIP ULTRA é um pneu de lonas cruzadas concebido para dumpers usados durante condições de serviço pesadas, tais como em aplicações de mineração, em pedreiras ou obras. O desenho não direcional do piso do pneu assegura uma ótima tração dianteira e lateral. O pneu é caracterizado por uma carcaça robusta de nylon com as juntas de ligação otimizadas e por um composto de borracha especial do piso que asseguram uma resistência extraordinária a cortes e lacerações, uma alta durabilidade e resistência ao desgaste, bem como ótimas qualidades de autolimpagem, mesmo em superficiais rochosas.

UM

International Standard

Construction

BIAS

Machinery

OTR: Camião basculante

Version	INDUSTRIAL
Type	TT
Tyre Size	12.00 - 24

Dimensions International Standard

Ply Rating	24
Overall Width (mm)	320
Overall Diameter (mm)	1250
Static Loaded Radius (mm)	585
Rolling Circumference (mm)	3710
Rim Rec	8.5
Rim Alt	8.0

Load capacity (Kg)

km/h / bar	8.20
50 LS/LD	4320

Printed on 03/05/2024 04:03

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..