

XL GRIP ULTRA - Dados técnicos



Description

XL GRIP ULTRA é um pneu de lonas cruzadas concebido para dumpers usados durante condições de serviço pesadas, tais como em aplicações de mineração, em pedreiras ou obras. O desenho não direcional do piso do pneu assegura uma ótima tração dianteira e lateral. O pneu é caracterizado por uma carcaça robusta de nylon com as juntas de ligação otimizadas e por um composto de borracha especial do piso que asseguram uma resistência extraordinária a cortes e lacerações, uma alta durabilidade e resistência ao desgaste, bem como ótimas qualidades de autolimpagem, mesmo em superficiais rochosas.

UM

US Standard

Construction



Machinery

OTR: Camião basculante

SIZE	Version	USACode	PR	RIM REC	RIM ALT	ow	OD	SLR	RC	Туре
10.00 - 20	STANDARD	94064205	18	7.5	7.0	11.2	42.3	19.9	128.2	TT
11.00 - 20	STANDARD	94064212	18	8.0	7.5	11.7	43.9	20.8	132.6	TT
12.00 - 20	STANDARD	94069569	20	8.5	8.0	12.6	45.5	21.5	136.4	TT
12.00 - 24	INDUSTRIAL	94060856	24	8.5	8.0	12.6	49.2	23	146.1	TT
12.00 - 24	STANDARD	94057467	20	8.5	8.0	12.6	49.2	23	146.1	TT

Printed on 02/05/2024 23:47

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..