

AGRIMAX RT 600 - Specificații tehnice

Descriere

AGRIMAX RT 600 este anvelopa ideală pentru pajiști, recoltare și împrăștiere. Datorită suprafeței mari de contact, AGRIMAX RT 600 asigură o distribuție excelentă a presiunii pe sol, reducând deteriorarea pajiștilor și protejând solul. Datorită tehnologiei de muchie rotundă, talonului ranforsat și numărului crescut de caneluri, garantează o stabilitate și tracțiune deosebite.

UM

US Standard

Construcție

 RADIAL

Mașinării

Agricultură: Mașină de recoltare • Mașină de împrăștiat • Tractor



| | |
|-----------------------|--------------|
| Versiune | STANDARD |
| Tip | TL |
| Dimensiunea anvelopei | 900/60 R 32 |
| LI/SS | 181 A8/178 B |

Dimensiuni US Standard

| | |
|------------------------------|-------------------|
| Usa code | 94062423 |
| Lățimea secțiunii (inch) | 35.3 |
| Overall Diameter (inch) | 74.5 |
| Static Loaded Radius (inch) | 33.1 |
| Rolling Circumference (inch) | 224.3 |
| Rim Rec | DW 27 B |
| Rim Alt | DW 28 B ; DW 30 B |
| ECE | E11-106R-005768 |

Load capacity (lbs)

| mph / psi | 12 | 15 | 17 | 20 | 23 | 29 | 35 | 41 | 46 | 49 | 55 |
|-----------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 30 | 7440 | 8430 | 9590 | 10580 | 11740 | 13060 | 14050 | 15380 | 16530 | - | - |
| 25 | 8190 | 9280 | 10550 | 11640 | 12920 | 14370 | 15460 | 16920 | 18190 | - | - |
| 20 | 8760 | 9930 | 11300 | 12470 | 13820 | 15390 | 16560 | 18110 | 19470 | - | - |
| 5 LT | 10970 | 12430 | 14140 | 15610 | 17310 | 19260 | 20720 | 22670 | 24370 | - | - |
| 5 HT | 8760 | 9930 | 11300 | 12470 | 13820 | 15390 | 16560 | 18110 | 19470 | - | - |
| 5 Cyc. | - | 14910 | 16950 | 18710 | 20760 | 23090 | 24840 | 27180 | 29220 | 29680 | 30920 |

Imprimat pe 4/18/2024 9:27 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..