

## AGRIMAX RT 945 - Specificații tehnice



### Descriere

AGRIMAX RT 945 este special concepută pentru culturile pe rânduri: nu dăunează culturilor și conservă producția. Caracteristicile excelente de auto-curățare permit o trecere rapidă de la operațiunile pe câmp la utilizarea pe șosea, unde AGRIMAX RT 945 demonstrează performanțe extraordinare. Carcasa puternică oferă anvelopei stabilitate excelentă, tracțiune remarcabilă și durabilitate excepțională.

### UM

Standard internațional

### Construcție

 RADIAL

### Mașinării

Agricultură: Pulverizator • Tractor

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	380/90 R 50 (14.9 R 50)
LI/SS	160A8/B

## Dimensiuni Standard internațional

Lățimea secțiunii (mm)	390
Overall Diameter (mm)	1954
Static Loaded Radius (mm)	921
Rolling Circumference (mm)	5958
SRI (mm)	950
Rim Rec	W 12
Rim Alt	W 11 ; W 13
ECE	E11-106R-006446
TRA Code	R1W

## Load capacity (Kg)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.4
50	1845	2385	2880	3195	3375	3690	4005	4275	4500	---
40	1845	2385	2880	3195	3375	3690	4005	4275	4500	---
30	1975	2555	3085	3420	3615	3950	4290	4575	4815	---
10	2670	3450	4165	4620	4880	5335	5790	6180	6505	6750

Imprimat pe 5/29/2023 10:48 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..