AGRIMAX RT 955 - Specificații tehnice

Descriere

AGRIMAX RT 955 este o anvelopă radială BKT pentru aplicații în culturi pe rânduri, în timp ce unele dimensiuni sunt potrivite și pentru pulverizare și podgorii. Designul special al benzii de rulare cu muchia rotunjită oferă performanțe excelente de tracțiune, stabilitate și proprietăți de auto-curățare. Datorită carcasei sale puternice, AGRIMAX RT 955 are o capacitate mare de încărcare.

UM

US Standard

Construcție

RADIAL

Mașinării

Agricultură: Pulverizator • Mașină de recoltat podgorii

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	210/95 R 32 (8.3 R 32)
LI/SS	120 A8/B

Dimensiuni US Standard

Usa code	94040018
Lățimea secțiunii (inch)	8.4
Overall Diameter (inch)	47.8
Static Loaded Radius (inch)	22.5
Rolling Circumference (inch)	145.8
Rim Rec	W 7
Rim Alt	W 6
ECE	E4-106R-001391
TRA Code	R1

Load capacity (lbs)

mph / psi	12	17	23	29	35	41	46	52
30	1420	1830	2230	2410	2620	2880	3090	-
25	1420	1830	2230	2410	2620	2880	3090	-
20	1520	1950	2380	2580	2810	3080	3310	-
5	2000	2600	3150	3430	3660	4030	4350	4630

Imprimat pe 5/5/2024 2:35 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..