

AGRIMAX RT 955 - Specificații tehnice



Descriere

AGRIMAX RT 955 este o anvelopă radială BKT pentru aplicații în culturi pe rânduri, în timp ce unele dimensiuni sunt potrivite și pentru pulverizare și podgorii. Designul special al benzii de rulare cu muchia rotunjită oferă performanțe excelente de tracțiune, stabilitate și proprietăți de auto-curățare. Datorită carcasei sale puternice, AGRIMAX RT 955 are o capacitate mare de încărcare.

UM

US Standard

Construcție

 RADIAL

Mașinării

Agricultură: Pulverizator • Mașină de recoltat podgorii

| | |
|-----------------------|---------------------------|
| Versiune | STANDARD |
| Tip | TL |
| Dimensiunea anvelopei | 230/95 R 36 (9.5 R 36) |
| LI/SS | 130 A8/B |

Dimensiuni US Standard

| | |
|------------------------------|----------------|
| Usa code | 94027477 |
| Lățimea secțiunii (inch) | 9.4 |
| Overall Diameter (inch) | 53.2 |
| Static Loaded Radius (inch) | 25.2 |
| Rolling Circumference (inch) | 161.9 |
| Rim Rec | W 8 |
| Rim Alt | W 7 |
| ECE | E4-106R-000765 |
| TRA Code | R1 |

Load capacity (lbs)

| mph / psi | 12 | 17 | 23 | 29 | 35 | 41 | 46 | 52 | 58 | 64 |
|-----------|------|------|------|------|------|------|------|------|------|------|
| 30 | 1640 | 2140 | 2600 | 2850 | 3020 | 3320 | 3600 | 3900 | 4180 | - |
| 25 | 1640 | 2140 | 2600 | 2850 | 3020 | 3320 | 3600 | 3900 | 4180 | - |
| 20 | 1750 | 2290 | 2790 | 3050 | 3240 | 3550 | 3870 | 4180 | 4490 | - |
| 5 | 1950 | 2460 | 3020 | 3580 | 4160 | 4280 | 4780 | 5280 | 5790 | 6280 |

Imprimat pe 4/26/2024 5:10 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..