

## AGRIMAX RT 955 - Fișa de date



### Descriere

AGRIMAX RT 955 este o anvelopă radială BKT pentru aplicații în culturi pe rânduri, în timp ce unele dimensiuni sunt potrivite și pentru pulverizare și podgorii. Designul special al benzii de rulare cu muchia rotunjită oferă performanțe excelente de tracțiune, stabilitate și proprietăți de auto-curățare. Datorită carcasei sale puternice, AGRIMAX RT 955 are o capacitate mare de încărcare.

### UM

US Standard

### Construcție

 RADIAL

### Mașinării

Agricultură: Pulverizator • Mașină de recoltat podgorii

SIZE	Version	USACode	TRA Code	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
<b>210/90 R 24 (8.3 R 24)</b>	STANDARD	94042531	R1	107 A8/B	W 7	W 6	8.4	39.8	18.2	119.2	TL	E4-106R-001818
<b>210/95 R 28 (8.3 R 28)</b>	STANDARD	94042548	R1	116 A8/B	W 7	W 6	8.4	43.7	20.2	132.4	TL	E4-106R-001819
<b>210/95 R 32 (8.3 R 32)</b>	STANDARD	94040018	R1	120 A8/B	W 7	W 6	8.4	47.8	22.5	145.8	TL	E4-106R-001391
<b>230/95 R 32 (9.5 R 32)</b>	STANDARD	94026678	R1	128 A8/B	W 7	W 8	9	49.3	23	150	TL	E4-106R-000764
<b>270/95 R 32 (11.2 R 32)</b>	STANDARD	94021857	R1	136 A8/B	W 9	W 8 ; W 10	10.8	52.2	24.2	160.5	TL	E4-106R-000776
<b>230/95 R 36 (9.5 R 36)</b>	STANDARD	94027477	R1	130 A8/B	W 8	W 7	9.4	53.2	25.2	161.9	TL	E4-106R-000765
<b>270/80 R 36</b>	STANDARD	94067046	R1	134 A8/B	W9	W8; W10	10.8	53	24.8	161	TL	E11-106R-006758
<b>270/95 R 36 (11.2 R 36)</b>	STANDARD	94027484	R1	139 A8/B	W 9	W 8 ; W 10	10.8	56.2	26.2	170.7	TL	E4-106R-000659
<b>270/95 R 38 (11.2 R 38)</b>	STANDARD	94028139	R1	140 A8/B	W 9	W 8 ; W 10	10.8	58.2	27.4	177.6	TL	E4-106R-000657
<b>230/95 R 40 (9.5 R 40)</b>	STANDARD	94055210	R1	132 A8/B	W 7	W 8	9	57.2	27.2	175	TL	E11-106R-004066
<b>230/95 R 42 (9.5 R 42)</b>	STANDARD	94028610	R1	133 A8/B	W 8	W 7	9.4	59.3	28.1	180.9	TL	E4-106R-000772
<b>300/85 R 42 (11.2 R 42)</b>	STANDARD	94040636	R1	144 A8/B	W 9	W 10 ; W 11	11.6	62.1	29.3	190.9	TL	E4-106R-001396
<b>210/95 R 44 (8.3 R 44)</b>	STANDARD	94042760	R1	120 A8/B	W 7	W 6	8.4	59.8	28.4	183.2	TL	E4-106R-000771
<b>230/95 R 44 (9.5 R 44)</b>	STANDARD	94027415	R1	134 A8/B	W 8	W 7	9.4	61.3	29.1	188.5	TL	E4-106R-000777
<b>270/95 R 44 (11.2 R 44)</b>	STANDARD	94028146	R1	142 A8/B	W 9	W 8 ; W 10	10.8	64.3	30.1	196.2	TL	E4-106R-00784
<b>270/95 R 46 (11.2 R 46)</b>	STANDARD	94042555	R1	143 A8/B	W 9	W 8 ; W 10	10.8	66.3	31.2	203.5	TL	E4-106R-000785
<b>300/95 R 46 (12.4 R 46)</b>	STANDARD	94021871	R1	148 A8/B	W 9	W 10 ; W 11 ; DW 10 ; DW 11	11.6	68.4	32	209.4	TL	E4-106R-000790
<b>340/85 R 46 (13.6 R 46)</b>	STANDARD	94044726	R1	150 A8/B	W 12	W 11	13.9	68.7	32.5	210.5	TL	E4-106R-001828
<b>230/95 R 48 (9.5 R 48)</b>	STANDARD	94021864	R1	136 A8/B	W 8	W 7	9.4	65.2	31.2	200.2	TL	E4-106R-000778
<b>230/95 R 48 (9.5 R 48)</b>	STANDARD	94052837	R1	136D/139A8	W 8	W 7	9.4	65.2	31.2	200.2	TL	E11-106R-004067
<b>270/95 R 48 (11.2 R 48)</b>	STANDARD	94021840	R1	144 A8/B	W 9	W 8 ; W 10	10.8	68.2	32.3	210.7	TL	E4-106R-000782
<b>340/85 R 48 (13.6 R 48)</b>	STANDARD	94059287	R1	151D/154A8	W 12	W 11	13.9	70.7	33.7	219.4	TL	E11-106R-005765
<b>340/85 R 48</b>	STANDARD	94029426	R1	152 A8/B	W 12	W 11	13.9	70.7	33.7	219.4	TL	E4-106R-000800

<b>(13.6 R 48)</b>												
<b>300/95 R 52 (12.4 R 52)</b>	STANDARD	94029747	R1	151 A8/B	W 9	W 10; W 11; DW 10; DW 11	11.6	74.4	35	227.3	TL	E4-106R-001484
<b>270/95 R 54 (11.2 R 54)</b>												
	STANDARD	94032839	R1	146 A8/B	W 9	W 8; W 10	10.8	74.2	35.2	228.9	TL	E4-106R-001410

Imprimat pe 4/26/2024 4:40 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..