

AGRIMAX SPARGO - Specificații tehnice



Descriere

AGRIMAX SPARGO este anvelopa specială BKT pentru aplicații de culturi pe rânduri. A fost concepută pentru creșterea productivității pe câmp și pentru conservarea solului pe termen lung. Datorită tehnologiei VF, anvelopa oferă o capacitate de încărcare mai mare la presiunea standard. Datorită carcasi puternice și unui număr mare de caneluri, AGRIMAX SPARGO asigură o durabilitate remarcabilă împreună cu o stabilitate puternică atât pe câmp, cât și în timpul transferurilor rutiere.

UM

Standard internațional

Construcție

 RADIAL

Mașinării

Agricultură: Pulverizator

| | |
|-----------------------|----------------|
| Versiune | STANDARD |
| Tip | TL |
| Dimensiunea anvelopei | VF 320/90 R 50 |
| LI/SS | 169 D |

Dimensiuni Standard internațional

| | |
|----------------------------|-------------------------------|
| Lățimea secțiunii (mm) | 323 |
| Overall Diameter (mm) | 1846 |
| Static Loaded Radius (mm) | 865 |
| Rolling Circumference (mm) | 5650 |
| SRI (mm) | 875 |
| Rim Rec | W 11 |
| Rim Alt | W 10 ; DW 10 ; W 10 L ; DW 11 |
| ECE | E11-106R-007204 |
| TRA Code | R1 |

Load capacity (Kg)

| km/h / bar | 1.2 | 1.4 | 1.6 | 1.8 | 2.0 | 2.2 | 2.4 | 2.6 | 2.8 | 3.0 | 3.2 | 3.4 | 3.6 | 3.8 | 4.0 | 4.2 | 4.4 | 4.8 |
|---------------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| 70 | 2415 | 2685 | 2955 | 3085 | 3220 | 3330 | 3435 | 3595 | 3760 | 3810 | 3865 | 4105 | 4350 | 4455 | 4565 | 4775 | 4990 | 5365 |
| From 65 to 40 | 2610 | 2900 | 3190 | 3335 | 3480 | 3600 | 3715 | 3890 | 4060 | 4120 | 4180 | 4440 | 4700 | 4815 | 4930 | 5165 | 5395 | 5800 |
| 30 | 2665 | 2960 | 3260 | 3405 | 3555 | 3675 | 3790 | 3970 | 4145 | 4205 | 4265 | 4530 | 4800 | 4915 | 5035 | 5270 | 5510 | 5920 |
| 20 | 2720 | 3020 | 3320 | 3475 | 3625 | 3745 | 3865 | 4045 | 4225 | 4285 | 4350 | 4620 | 4890 | 5010 | 5130 | 5375 | 5615 | 6035 |
| 10 | 2875 | 3190 | 3510 | 3670 | 3830 | 3960 | 4085 | 4275 | 4470 | 4530 | 4595 | 4885 | 5170 | 5300 | 5425 | 5680 | 5935 | 6380 |

Imprimat pe 4/23/2024 4:48 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..