

AGRIMAX SPARGO - Specificații tehnice



Descriere

AGRIMAX SPARGO este anvelopa specială BKT pentru aplicații de culturi pe rânduri. A fost concepută pentru creșterea productivității pe câmp și pentru conservarea solului pe termen lung. Datorită tehnologiei VF, anvelopa oferă o capacitate de încărcare mai mare la presiunea standard. Datorită carcasi puternice și unui număr mare de caneluri, AGRIMAX SPARGO asigură o durabilitate remarcabilă împreună cu o stabilitate puternică atât pe câmp, cât și în timpul transferurilor rutiere.

UM

US Standard

Construcție

 RADIAL

Mașinării

Agricultură: Pulverizator

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	VF 480/80 R 46
LI/SS	177 D

Dimensiuni US Standard

Usa code	94057306
Lățimea secțiunii (inch)	18.9
Overall Diameter (inch)	76.2
Static Loaded Radius (inch)	35.1
Rolling Circumference (inch)	232.6
Rim Rec	DW 16 L
Rim Alt	DW 15 L
ECE	E11-106R-004756
TRA Code	R1

Load capacity (lbs)

mph / psi	17	20	23	26	29	32	35	38	41	44	47	49	52
45	8190	9080	9960	10390	10980	11270	11570	12150	12740	13180	13760	14200	14640
from 40 to 25	9010	9980	10940	11420	12070	12390	12710	13350	14000	14490	15130	15610	16100
20	9190	10180	11160	11660	12310	12640	12970	13620	14280	14780	15430	15920	16420
12	9370	10380	11380	11880	12550	12880	13220	13880	14550	15060	15720	16230	16740
5	9910	10970	12040	12570	13280	13630	13980	14690	15400	15930	16640	17170	17710

Imprimat pe 4/17/2024 8:53 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..