

AIROMAX AM 27 - Specificații tehnice



Descriere

AIROMAX AM 27 este anvelopa ideală pentru șosea pentru aplicații în construcții cu macarale. Are o rezistență extraordinară la căldură și un confort remarcabil la călătorie. AIROMAX AM 27 este o anvelopă de mare viteză potrivită în special pentru toate operațiunile care necesită un nivel ridicat de manevrabilitate.

UM

Standard internațional

Construcție

 RADIAL

Mașinării

Industrial: Macara mobilă

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	525/80 R 25 (20.5 R 25)
LI/SS	176 F

Dimensiuni Standard internațional

Overall Width (mm)	530
Overall Diameter (mm)	1481
Static Loaded Radius (mm)	681
Rolling Circumference (mm)	4534
Rim Rec	17.00/2.0
Rim Alt	17.00/1.7 CR
ECE	E11-54R-0016681

Load capacity (Kg)

km/h / bar	5.25	5.50	5.75	6.00	6.25	6.50	6.75	7.00
80	5600	5800	6000	6300	6500	6700	6900	7100

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Imprimat pe 5/11/2025 12:57 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..