

AIROMAX AM 543 - Specificații tehnice



Descriere

AIROMAX AM 543 este anvelopa ideală pentru aplicații în construcții cu macarale. Prezintă tracțiune remarcabilă și stabilitate ridicată. Deoarece anvelopele macaralei sunt supuse unui stres deosebit și condițiilor extreme de utilizare, AIROMAX AM 543 a fost proiectată pentru a oferi o rezistență excelentă la căldură. În plus, este potrivită pentru toate operațiunile care necesită un nivel ridicat de manipulare.

UM

US Standard

Construcție

 RADIAL

Mașinării

Industrial: Macara mobilă

Versiune	STANDARD
Tip	TT
Dimensiunea anvelopei	385/95 R 24 (14.00 R 24)
LI/SS	170 E

Dimensiuni US Standard

Usa code	94064502
Overall Width (inch)	14.8
Overall Diameter (inch)	53.3
Static Loaded Radius (inch)	24.7
Rolling Circumference (inch)	163.6
Rim Rec	10.00W

Load capacity (lbs)

mph / psi	130
43	13200

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Imprimat pe 2/9/2025 4:35 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..