

AIROMAX AM 543 - Specificații tehnice



Descriere

AIROMAX AM 543 este anvelopa ideală pentru aplicații în construcții cu macarale. Prezintă tracțiune remarcabilă și stabilitate ridicată. Deoarece anvelopele macaralei sunt supuse unui stres deosebit și condițiilor extreme de utilizare, AIROMAX AM 543 a fost proiectată pentru a oferi o rezistență excelentă la căldură. În plus, este potrivită pentru toate operațiunile care necesită un nivel ridicat de manipulare.

UM

Standard internațional

Construcție

 RADIAL

Mașinării

Industrial: Macara mobilă

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	445/95 R 25 (16.00 R 25)
LI/SS	177 E

Dimensiuni Standard internațional

Overall Width (mm)	435
Overall Diameter (mm)	1480
Static Loaded Radius (mm)	670
Rolling Circumference (mm)	4502
Rim Rec	11.25/2.0
Rim Alt	11.00/1.7 CR ; 11.00/1.7CRL

Load capacity (Kg)

km/h / bar	9.00
30	9500
40	9000
50	8500
60	8175
70	7300
80	6000
90	5150
100	4375

Imprimat pe 4/27/2024 10:57 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..