

AS 504 - Specificații tehnice



Descriere

AS 504 este o anvelopă agroindustrială concepută în principal pentru cultivarea solului, utilaje și manipulare a materialelor. Această anvelopă, care are proprietăți excelente de auto-curățare și aderență sporită, este potrivită pentru remorci de câmp și manipuloare telescopice. AS 504 este disponibilă în mai multe versiuni pentru a satisface cerințele specifice ale utilizatorului final: o versiune "HD" cu un compus special rezistent la tăiere și așchiere, în timp ce versiunea "specială" are o carcasă ranforsată care asigură o durată de viață mai lungă a anvelopei.

UM

US Standard

Construcție

 BIAS

Mașinării

Agricultură: Încărcător telescopic • Remorcă de câmp
Industrial: Încărcător telescopic

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	10.0/75 - 15.3
LI/SS DRIVE WHEEL	111 A8
LI/SS FREE ROLLING	123 A8

Dimensiuni US Standard

Usa code	94018567
Rating de sarcină	10
Lățimea secțiunii (inch)	10.4
Overall Diameter (inch)	30.9
Static Loaded Radius (inch)	14.2
Rolling Circumference (inch)	94.6
Rim Rec	9.00
ECE	E4-106R-001812

Load capacity (lbs)

mph / psi	57
5 FR	4780
15 FR	4070
20 FR	3820
25 FR	3420
5 DW	3360
15 DW	2850
20 DW	2690
25 DW	2400

Imprimat pe 4/20/2024 12:42 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..