

AS 504 - Specificații tehnice



Descriere

AS 504 este o anvelopă agroindustrială concepută în principal pentru cultivarea solului, utilaje și manipulare a materialelor. Această anvelopă, care are proprietăți excelente de auto-curățare și aderență sporită, este potrivită pentru remorci de câmp și manipuloare telescopice. AS 504 este disponibilă în mai multe versiuni pentru a satisface cerințele specifice ale utilizatorului final: o versiune "HD" cu un compus special rezistent la tăiere și așchiere, în timp ce versiunea "specială" are o carcasă ranforsată care asigură o durată de viață mai lungă a anvelopei.

UM

Standard internațional

Construcție

 BIAS

Mașinării

Agricultură: Încărcător telescopic • Remorcă de câmp
Industrial: Încărcător telescopic

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	15.5/80 - 24
LI/SS DRIVE WHEEL	142 A8
LI/SS FREE ROLLING	154 A8

Dimensiuni Standard internațional

Rating de sarcină	10
Lățimea secțiunii (mm)	384
Overall Diameter (mm)	1262
Static Loaded Radius (mm)	570
Rolling Circumference (mm)	3875
SRI (mm)	600
Rim Rec	W 12
Rim Alt	W 13 ; W 14 L
ECE	E11-106R-004349

Load capacity (Kg)

km/h / bar	2.50
10 FR	5250
25 FR	4465
30 FR	4200
40 FR	3750
10 DW	3710
25 DW	3155
30 DW	2970
40 DW	2650

Imprimat pe 4/20/2024 1:43 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..