

AS 504 - Specificații tehnice



Descriere

AS 504 este o anvelopă agroindustrială concepută în principal pentru cultivarea solului, utilaje și manipulare a materialelor. Această anvelopă, care are proprietăți excelente de auto-curățare și aderență sporită, este potrivită pentru remorci de câmp și manipuloare telescopice. AS 504 este disponibilă în mai multe versiuni pentru a satisface cerințele specifice ale utilizatorului final: o versiune "HD" cu un compus special rezistent la tăiere și așchiere, în timp ce versiunea "specială" are o carcasă ranforsată care asigură o durată de viață mai lungă a anvelopei.

UM

US Standard

Construcție

 BIAS

Mașinării

Agricultură: Încărcător telescopic • Remorcă de câmp
Industrial: Încărcător telescopic

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	15.5/80 - 24
LI/SS DRIVE WHEEL	151 A8
LI/SS FREE ROLLING	163 A8

Dimensiuni US Standard

Usa code	94019007
Rating de sarcină	16
Lățimea secțiunii (inch)	15.1
Overall Diameter (inch)	49.7
Static Loaded Radius (inch)	22.4
Rolling Circumference (inch)	152.6
Rim Rec	W 12
Rim Alt	W 13 ; W 14 L
ECE	E4-106R-002265

Load capacity (lbs)

mph / psi	58
5 FR	15050
15 FR	12790
20 FR	12040
25 FR	10750
5 DW	10650
15 DW	9050
20 DW	8520
25 DW	7610

Imprimat pe 4/20/2024 2:58 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..