

AS 504 - Specificații tehnice



Descriere

AS 504 este o anvelopă agroindustrială concepută în principal pentru cultivarea solului, utilaje și manipulare a materialelor. Această anvelopă, care are proprietăți excelente de auto-curățare și aderență sporită, este potrivită pentru remorci de câmp și manipuloare telescopice. AS 504 este disponibilă în mai multe versiuni pentru a satisface cerințele specifice ale utilizatorului final: o versiune "HD" cu un compus special rezistent la tăiere și așchiere, în timp ce versiunea "specială" are o carcasă ranforsată care asigură o durată de viață mai lungă a anvelopei.

UM

Standard internațional

Construcție

BIAS

Mașinării

Agricultură: Încărcător telescopic, Remorcă de câmp
Industrial: Încărcător telescopic

Versiune	STANDARD
Tip	TT
Dimensiunea anvelopei	7.50 - 20
LI/SS DRIVE WHEEL	103 A8
LI/SS FREE ROLLING	116 A8

Dimensiuni Standard internațional

Rating de sarcină	8
Lățimea secțiunii (mm)	209
Overall Diameter (mm)	904
Static Loaded Radius (mm)	422
Rolling Circumference (mm)	2695
SRI (mm)	425
Rim Rec	5.50 F
Rim Alt	4.50 E ; 6.00 F ; 5.00 F
ECE	E4-106R-002636

Load capacity (Kg)

km/h / bar	3.20
10 FR	1750
25 FR	1490
30 FR	1400
40 FR	1250
10 DW	1225
25 DW	1040
30 DW	980
40 DW	875

Imprimat pe 04/12/2022 02:22

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..