

## AS 505 - Specificații tehnice



### Descriere

AS 505 este ideală pentru operațiunile de cultivare a solului cu remorci și utilaje. Are proprietăți excelente de auto-curățare și tracțiune sporită pe sol, în special pe sol noroios. Anvelopa are, de asemenea, un ciclu lung de viață.

### UM

US Standard

### Construcție

 BIAS

### Mașinării

Agricultură: Mașini de implementare • Remorță

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	6.5/80 - 15
LI/SS DRIVE WHEEL	86 A8
LI/SS FREE ROLLING	98 A8

## Dimensiuni US Standard

Usa code	94019465
Rating de sarcină	6
Lățimea secțiunii (inch)	6.7
Overall Diameter (inch)	27.4
Static Loaded Radius (inch)	12.8
Rolling Circumference (inch)	82.9
Rim Rec	5.0
Rim Alt	4½ K ; 5 K ; 5 J
ECE	E4-106R-002188

## Load capacity (lbs)

mph / psi	52
5 FR	2310
15 FR	1970
20 FR	1850
25 FR	1650
5 DW	1630
15 DW	1390
20 DW	1310
25 DW	1170

Imprimat pe 4/25/2024 5:37 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..