

AS 509 - Fișa de date



Descriere

AS 509 a fost special concepută pentru remorci, prese de balotat și utilaje. Acesta asigură o capacitate mare de încărcare la presiune scăzută de umflare, protejând culturile. AS 509 oferă proprietăți excelente de tracțiune și auto-curățare.

UM

Standard internațional

Construcție

❖ BIAS

Mașinării

Agricultură: Presă de balotat • Mașini de implementare • Remorcă

SIZE	Version	LI/SS DRIVE WHEEL	LI/SS FREE ROLLING	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
550/45 - 22.5	STANDARD	141 A8/137 B	153 A8/149 B	12	AG 16.00		540	1065	479	3250	TL	E11-106R-006445
550/45 - 22.5	STANDARD	154 A8/150 B	166 A8/162 B	20	AG 16.00		540	1065	479	3250	TL	E11-106R-004545

Imprimat pe 4/20/2024 4:17 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..