

AS 511 - Specificații tehnice



Descriere

AS 511 este cea mai potrivită anvelopă pentru operațiunile pe pajiști cu utilaje. Carcasa robustă și compusul special al benzii de rulare rezistent la tăiere asigură o stabilitate extraordinară și o performanță îmbunătățită. Datorită suprafeței mari de contact, AS 511 asigură o tracțiune excelentă și minimizează compactarea solului.

UM

US Standard

Construcție

 RADIAL

Mașinării

Agricultură: Mașini de implementare

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	31 X 15.50 R 15

Dimensiuni US Standard

Usa code	94059782
Lățimea secțiunii (inch)	15.3
Overall Diameter (inch)	30.9
Static Loaded Radius (inch)	13.9
Rolling Circumference (inch)	94
Rim Rec	13 LB
ECE	E11-106R-005098

Load capacity (lbs)

mph / psi	41
30	3305

Imprimat pe 6/8/2023 1:56 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..