

AS 511 - Specificații tehnice



Descriere

AS 511 este cea mai potrivită anvelopă pentru operațiunile pe pajiști cu utilaje. Carcasa robustă și compusul special al benzii de rulare rezistent la tăiere asigură o stabilitate extraordinară și o performanță îmbunătățită. Datorită suprafetei mari de contact, AS 511 asigură o trașiune excelentă și minimizează compactarea solului.

UM

US Standard

Construcție

 RADIAL

Mașinării

Agricultură: Mașini de implementare

| | |
|-----------------------|-----------------|
| Versiune | STANDARD |
| Tip | TL |
| Dimensiunea anvelopei | 31 X 15.50 R 15 |

Dimensiuni US Standard

| | |
|------------------------------|-----------------|
| Usa code | 94059782 |
| Lățimea secțiunii (inch) | 15.3 |
| Overall Diameter (inch) | 30.9 |
| Static Loaded Radius (inch) | 13.9 |
| Rolling Circumference (inch) | 94 |
| Rim Rec | 13 LB |
| ECE | E11-106R-005098 |

Load capacity (lbs)

| | |
|-----------|------|
| mph / psi | 41 |
| 30 | 3305 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Imprimat pe 5/13/2025 12:31 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..