

AT 110 - Specificații tehnice



Descriere

AT 110 este anvelopa BKT potrivită pentru aplicații pe toate terenurile cu ATV-uri. Datorită controlului extraordinar al direcției, AT 110 este anvelopa ideală pentru axul față al vehiculului.

UM

Standard internațional

Construcție

 BIAS

Mașinării

Agricultură: ATV

| | |
|-----------------------|----------------|
| Versiune | STANDARD |
| Tip | TL |
| Dimensiunea anvelopei | AT 21 X 7 - 10 |

Dimensiuni Standard internațional

| | |
|------------------------|--------|
| Rating de sarcină | 4 |
| Lățimea secțiunii (mm) | 178 |
| Overall Diameter (mm) | 531 |
| Rim Rec | 5.5 AT |
| Rim Alt | 6.0 AT |

Load capacity (Kg)

| | |
|------------|------|
| km/h / bar | 0.35 |
| 100 | 93 |

Imprimat pe 4/26/2024 6:18 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..