

## AT 625 - Fișa de date



### Descriere

LA 625 este potrivită pentru buldoexcavatoare și încărcătoare compacte în toate operațiunile agricole de săpat și încărcare. Banda de rulare extra adâncă asigură rezistență și durabilitate sporite la perforare. AT 625 oferă o tracțiune și stabilitate excelente, precum și o rezistență îmbunătățită la tăiere și așchiere. &nbsp;

### UM

Standard internațional

### Construcție

 BIAS

### Mașinării

Industrial: Buldoexcavator • Încărcător compact

SIZE	Version	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type
14.9 - 24	STANDARD	R4	145 A8	12	DW 13	DW 11 ; DW 12 ; DW 13 L	400	1265	575	3800	TL
14.9 - 24	STANDARD	R4	145 A8	12	DW 13	DW 11 ; DW 12 ; DW 13 L	400	1265	575	3800	TT
16.9 - 28	INDUSTRIAL	R4	152 A8	12	DW 15 L	DW 14 L	450	1415	645	4254	TL
16.9 - 28	INDUSTRIAL	R4	152 A8	12	DW 15 L	DW 14 L	450	1415	645	4254	TT
16.9 - 28	SPECIAL	R4	152 A8	12	DW 15 L	DW 14 L	450	1415	645	4254	TT

Imprimat pe 4/28/2024 2:46 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..