

## AW 705 - Specificații tehnice



### Descriere

AW 705 a fost dezvoltată pentru utilaje, remorci și prese de balotat în aplicații de cultivare a solului și transport. Este ideală pentru agricultura modernă datorită durabilității îmbunătățite și capacității mari de încărcare.

### UM

US Standard

### Construcție

 BIAS

### Mașinării

Agricultură: Presă de balotat • Mașini de implementare • Remorcă

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	14.0/65 - 16
LI/SS FREE ROLLING	142 A8

## Dimensiuni US Standard

Usa code	94009930
Rating de sarcină	14
Lățimea secțiunii (inch)	13.9
Overall Diameter (inch)	34.3
Static Loaded Radius (inch)	15.3
Rolling Circumference (inch)	100.4
Rim Rec	11.0
ECE	E4-106R-001901

## Load capacity (lbs)

mph / psi	58
5 FR	8180
15 FR	6960
20 FR	6550
25 FR	5840

Imprimat pe 4/26/2024 11:36 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..