

AW 705 - Specificații tehnice



Descriere

AW 705 a fost dezvoltată pentru utilaje, remorci și prese de balotat în aplicații de cultivare a solului și transport. Este ideală pentru agricultura modernă datorită durabilității îmbunătățite și capacității mari de încărcare.

UM

US Standard

Construcție

 BIAS

Mașinării

Agricultură: Presă de balotat • Mașini de implementare • Remorcă

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	15.0/55 - 17
LI/SS FREE ROLLING	146 A8

Dimensiuni US Standard

Usa code	94010097
Rating de sarcină	18
Lățimea secțiunii (inch)	15
Overall Diameter (inch)	33.5
Static Loaded Radius (inch)	15.4
Rolling Circumference (inch)	101.4
Rim Rec	13.00
Rim Alt	13 ; W 13
ECE	E4-106R-001882

Load capacity (lbs)

mph / psi	68
5 FR	9260
15 FR	7870
20 FR	7410
25 FR	6610

Imprimat pe 4/26/2024 9:47 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..