

AW 708 - Specificații tehnice



Descriere

AW 708 a fost dezvoltată pentru cultivarea solului, transport și recoltarea fânului cu utilaje, remorci și prese de balotat. Este disponibilă o versiune HD cu un compus special rezistent la tăiere și așchiere.

UM

US Standard

Construcție

 BIAS

Mașinării

Agricultură: Presă de balotat • Mașini de implementare • Remorcă
Industrial: Remorcă

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	400/60 - 15.5
LI/SS FREE ROLLING	149 A8

Dimensiuni US Standard

Usa code	94010356
Rating de sarcină	18
Lățimea secțiunii (inch)	15.9
Overall Diameter (inch)	34.4
Static Loaded Radius (inch)	15
Rolling Circumference (inch)	100.9
Rim Rec	AG 13.00
ECE	E4-106R-001543

Load capacity (lbs)

mph / psi	65
5 FR	10030
15 FR	8530
20 FR	8020
25 FR	7160

Imprimat pe 4/24/2024 4:34 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..