

AW 708 - Specificații tehnice

Descriere

AW 708 a fost dezvoltată pentru cultivarea solului, transport și recoltarea fânului cu utilaje, remorci și prese de balotat. Este disponibilă o versiune HD cu un compus special rezistent la tăiere și așchiere.

UM

Standard internațional

Construcție

 BIAS

Mașinării

Agricultură: Presă de balotat • Mașini de implementare •
Remorcă
Industrial: Remorcă



Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	500/50 - 17
LI/SS FREE ROLLING	149 A8

Dimensiuni Standard internațional

Rating de sarcină	14
Lățimea secțiunii (mm)	500
Overall Diameter (mm)	945
Static Loaded Radius (mm)	416
Rolling Circumference (mm)	2750
Rim Rec	16.00
ECE	E4-106R-001813

Load capacity (Kg)

km/h / bar	2.80
10 FR	4550
25 FR	3870
30 FR	3640
40 FR	3250

Imprimat pe 4/24/2024 8:25 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..